From Lucian Stancu's presentation on cross-platform ransomware, this timeline follows the many pivots and stages of development of the various ransomware families, from the early days of Locker ransomware to the current era of Ransomware-as-a-Service and double-extortion schemes.

GET LATEST MALWARE

CYBER EMPIRE OF CRYPTO RANSOMWARE

Part I

Presented at the prestigious 40th anniversary of the Jewish Library and Center for Holocaust Studies in Buenos Aires, Argentina, Lucian Stancu, a senior researcher at Bitdefender, has compiled a timeline of the many pivots and stages of development of the various ransomware families, from the early days of Locker ransomware to the current era of Ransomware-as-a-Service and double-extortion schemes.

Ransomware is a type of malware that maliciously encrypts victim's data and demands a ransom payment to restore access to the data upon payment of a ransom. The data is encrypted using strong cryptographic algorithms, making it impossible for victims to recover their files without the decryption key. Ransomware attacks can cause significant disruption to individuals and organizations, as they can result in the loss of important data, financial losses, and damage to reputation.

Ransomware can be broadly categorized into two main types: locker ransomware and crypto ransomware.

Locker Ransomware

This type of ransomware locks the victim's device or system, preventing them from accessing it. It typically displays a ransom note on the victim's screen, demanding payment in exchange for a code to unlock the device.

Crypto Ransomware

This type of ransomware encrypts the victim's files, making them inaccessible without the decryption key. The ransom note usually appears on the victim's screen, demanding payment in exchange for the decryption key.

Ransomware can be distributed through various methods, including phishing emails, malicious attachments, drive-by downloads, and exploit kits. Once it infects a system, it can spread to other devices on the network, encrypting files on each device it infects.

Some well-known ransomware families include WannaCry, Petya, NotPetya, Ryuk, and Maze. Ransomware attacks have become increasingly sophisticated and targeted, with attackers often conducting reconnaissance on their victims before launching an attack.

Key trends

- The first **Locker ransomware** attacks started as early as 2005 and 2006 but were unsophisticated.
- Approximately **80%** of ransomware targets the Windows platform.
- Ransomware families such as **Petya**, **NotPetya**, **WannaCry**, **Conti**, and **Ryuk** have caused significant damage to organizations worldwide.
- The first **crypto ransomware** attacks started in 2013 with **CryptoLocker** and **CryptoWall**.
- Ransomware can be delivered through various methods, including **phishing emails**, **malicious attachments**, **drive-by downloads**, and **exploit kits**.
- Ransomware can spread to other devices on the network, encrypting files on each device it infects.
- The number of Ransomware programs increased by **46%** in 2021.
- The number of Ransomware attacks increased by **105%** in 2021.
- Ransomware attacks can cause significant disruption to individuals and organizations, as they can result in the loss of important data, financial losses, and damage to reputation.
- Ransomware attacks have become increasingly sophisticated and targeted, with attackers often conducting reconnaissance on their victims before launching an attack.

Ransomware as a service: a new criminal model which fosters increased operations in 2020-2021

Ransomware-as-a-service (RaaS) is a business model in which cybercriminals develop and distribute ransomware to affiliates, who then use it to carry out attacks. The affiliates pay a fee to the developers for access to the ransomware and a share of the profits from successful attacks.

RaaS has become a popular way for cybercriminals to launch ransomware attacks, as it allows them to outsource the development and distribution of the ransomware to specialized groups. This can make it easier for cybercriminals to launch attacks, as they do not need to have the technical expertise to develop their own ransomware.

RaaS has also made it more difficult for law enforcement to track down and prosecute ransomware attackers, as the developers of the ransomware are often located in different countries than the affiliates who use it.

Ransomware-as-a-service (RaaS) is a business model in which cybercriminals develop and distribute ransomware to affiliates, who then use it to carry out attacks. The affiliates pay a fee to the developers for access to the ransomware and a share of the profits from successful attacks.

RaaS has become a popular way for cybercriminals to launch ransomware attacks, as it allows them to outsource the development and distribution of the ransomware to specialized groups. This can make it easier for cybercriminals to launch attacks, as they do not need to have the technical expertise to develop their own ransomware.

RaaS has also made it more difficult for law enforcement to track down and prosecute ransomware attackers, as the developers of the ransomware are often located in different countries than the affiliates who use it.

History of the emergence of a new criminal world and which moved quickly between 1989-2021

Date	Event
01.1989	The first **Locker ransomware** attack was launched by Joseph Popp.
12.2005	The emergence of the first known Locker ransomware.
12.2006	The emergence of the first known modern PC/Trojan Locker ransomware.
01.2013	The first **crypto ransomware** attacks started with **CryptoLocker**.
01.2013	The first **crypto ransomware** attacks started with **CryptoWall**.
01.2014	The first appearance of the Simplocker Locker, an emergence and the beginning of the Android ransomware era.
01.2015	The first appearance of **TeslaCrypt**.
01.2016	The first appearance of the first known affiliate program.
01.2016	The first appearance of **Locky** ransomware.
01.2017	The first appearance of **WannaCry**.
01.2017	The appearance of a basic API ransomware.
01.2017	The appearance of a basic API ransomware.
01.2017	The appearance of a basic API ransomware